Low Energy LED Site Lighting

Electrical

Theses two lights feature a quick release system which allows the lamps to be removed from the tripod for use as pod lights. Twist grip locks extend the tripod. An adjustable leg allows easy levelling on uneven surfaces.

AITHFUL

elescopic 960mm - 1885mm ////////////

A quick release allows lights to be easily used as pod lights.

4200

LUMENS

IP65

30W LED Single Tripod Sitelight

2100

LUMENS

IP65

Adjustable height 960 -1885mm. 3 metre cable and approved plug.

240V FPPSLLED30T £115.68 Ex VAT £138.82 Inc VAT

110V FPPSLLED30TL £115.68 Ex VAT **£138.82** Inc VAT

60W LED Twin Tripod Sitelight

Adjustable height 960 -1885mm. 3 metre cable and approved plug.

240V FPPSLLED60T £212.77 Ex VAT £255.32 Inc VAT

IP Ratings

IP ratings indicate the level of protection against the ingress of water and dust into the product.

In general terms the higher the number the greater the protection.

First numeral Protection against ingress of solid foreign objects.

Second numeral Protection against harmful ingress of water.

IP ratings of Faithfull electrical products

IP20

- 2 Protection from solid objects approximately 12mm in size, such as adult fingers.
- No protection

IP44

- 4 The access probe of 1.0mm diameter shall not penetrate.
- 4 Protection against water splashed from all directions. (Limited ingress permitted).

IP54

- 5 Limited ingress of dust permitted (no harmful deposit).
- 4 Protection against water splashed from all directions. (Limited ingress permitted).

IP65

- **6** Total protection against ingress of dust.
- **5** Protection against low pressure jets of water from all directions. (Limited ingress permitted).