

TRANSFORMERS

Heavy-duty GPR waterproof cases rated to IP44 (where applicable). Re-settable thermal overload protection. Fitted with BS approved 13 amp plug. Fully weatherproof.

IN 240V

OUT 110V

Recommended Running Cycles
Intermittent duty 5min on / 15min off.
Not suitable for use on 110v heaters.

1.5kVA Single Outlet

Designed for use on the worksite to provide power to industrial power tools.

Lightweight 10.8kg

16 AMP

IP44

BSEN61558
Sockets are
BSEN60309



2M CABLE



- Intermittent rating: 1.5KVA
- Continuous rating: 0.9KVA
- Input: 240 volt 50Hz
- Output: 1 x 110 volt 16 amp

FPPTAN15
£92.80 Ex VAT
£111.36 Inc VAT

3.3kVA Twin Outlet

Includes a unique blue LED 'Power On' indicator, which provides the user with an 'at a glance' conformation that the unit is live.

Blue LEDs

16 AMP

IP44

BSEN61558
Sockets are
BSEN60309



2M CABLE



- Intermittent rating: 3.3KVA
- Continuous rating: 1.65KVA
- Input: 240 volt 50Hz
- Output: 2 x 110 volt 16 amp

FPPTAN33A
£96.81 Ex VAT
£116.17 Inc VAT

5.0kVA Triple Outlet

Front and rear mounted sockets. Suitable for use in most types of outdoor and worksite conditions.

3 Sockets

16 AMP

32 AMP

IP44

BSEN61558
Sockets are
BSEN60309



2M CABLE



- Intermittent rating: 5.0KVA
- Continuous rating: 2.8KVA
- Input: 240 volt 50Hz
- Output: 2 x 110 volt 16 amp
1 x 110 volt 32 amp

FPPTAN5
£301.63 Ex VAT
£361.96 Inc VAT

3.0kVA Vented Heater

110v vented portable transformer suitable for use with 110v electric heaters or other applications where a continuous load is to be applied.

16 AMP

32 AMP

IP20

BS3535
EN60742



2M CABLE



- Continuous rating: 3.0KVA
- Input: 240 volt 50Hz
- Output: 1 x 110 volt 16 amp
1 x 110 volt 32 amp

FPPTANHEAT
£418.92 Ex VAT
£502.70 Inc VAT